

Hinckley and Bosworth Borough Level 2 Strategic Flood Risk Assessment: Detailed Site Summary Tables



Site details	Site Code	Site LPR79 – Land north and west of Chapel Lane, Congerstone			
	Area	1.26 hectares			
	Current land use	Greenfield			
	Proposed land use	Residential			
Sources of flood risk	Existing drainage features	An unnamed drain flowing into the River Sence runs along the northern boundary of the site.			
	Fluvial	Proportion of site at risk			
		FZ3b	FZ3a	FZ2	FZ1
		7%	7%	9%	91%
	Fluvial flood risk to the site is associated with the drainage channel along the northern boundary. Flood Zones 3b, 3a and 2 begin to encroach into the site along the northern boundary. This is a widespread area of flooding to the north. Most of the site lies in Flood Zone 1.				
	Surface Water	Proportion of site at risk (RoFfSW)			
		30-year	100-year	1,000-year	
5%		5%	7%		
There is minimal risk of surface water flooding at this site. Surface water ponding begins to encroach into the site along the northern boundary in 30-year, 100-year, and 1,000-year events.					
Reservoir	The site is not shown to be at risk of reservoir flooding.				
Flood history	The site is not covered by the Environment Agency's historic flood map. There are no records of historic flooding at the site from Leicestershire County Council.				
Flood risk management infrastructure	Defences	Defence Type	Standard of Protection	Condition	
		-	-	-	
	This site is not protected by any formal flood defences.				
Residual risk	-				
Emergency planning	Flood warning	The area in the north of the site adjacent to the drainage channel falls within the River Anker and River Sence Flood Alert Area (033WAF307).			
	Access and egress	In all fluvial flooding events and the 30-year surface water flood event, access and egress is available via Barton Road if approaching from the south. Dry access and egress to the site is not possible in all surface water flooding events due to surface water ponding on Barton Lane to the north and south of the site, though this is not extensive. Depths in the 100-year surface water flood event along Barton Road to the south of the site are mostly 0-0.3m; however, isolated areas flood depths could reach up to 0.6m. The depths, velocities, hazards, durations and speeds of onset of surface water and fluvial flooding along access/ egress routes should be investigated further in a site-specific assessment, to confirm whether access for emergency vehicles could still be obtained.			

Hinckley and Bosworth Borough Level 2 Strategic Flood Risk Assessment: Detailed Site Summary Tables



Site details	Site Code	Site LPR79 – Land north and west of Chapel Lane, Congerstone			
	Area	1.26 hectares			
	Current land use	Greenfield			
	Proposed land use	Residential			
Climate Change	Climate change allowances for '2080s'	River Basin District	Central	Higher Central	Upper End
	Implications for the site	Humber	20%	30%	50%
Requirements for drainage control and impact mitigation	Broad scale assessment of possible SuDS	<p>Fluvial extents from climate change did not increase significantly when compared with FZ3a. As the site is affected by surface water flooding from the 100-year event, climate change may also increase the extent, depth and frequency of surface water flooding. The 1,000-year surface water extent can be used as an indication of surface water climate change extents.</p> <ul style="list-style-type: none"> • Geology at the site consists of: <ul style="list-style-type: none"> ○ Bedrock – Mudstone, siltstone and sandstone ○ Superficial – Diamicton • The site is not located within a Groundwater Source Protection Zone. • Most source control techniques are likely to be suitable. Mapping suggests that permeable paving may have to use non-infiltrating systems given the possible risk from groundwater. • Infiltration may be suitable. Mapping suggests a medium risk of groundwater flooding and underlying soils may be permeable. Further site investigation should be carried out to assess potential for drainage by infiltration. If infiltration is suitable it should be avoided in areas where the depth to the water table is <1m. • Mapping suggests that the site slopes are suitable for all forms of detention. A liner maybe required due to the site potential groundwater flooding. • All filtration techniques are likely to be suitable. A liner maybe required to prevent the egress of groundwater. • All forms of conveyance are likely to be suitable. Where the slopes are >5% features should follow contours or utilise check dams to slow flows. A liner maybe required to prevent the egress of groundwater. • The site is not designated by the Environment Agency as previously being a landfill site. • should refer to latest SuDS guidance on Leicestershire County Council's website and Environmental Best Practice notes as well as the Level 1 SFRA, for information on suitable types of SuDS, the management train and opportunities and constraints. 			

**Hinckley and Bosworth Borough Level 2
Strategic Flood Risk Assessment:
Detailed Site Summary Tables**



Site details	Site Code	Site LPR79 – Land north and west of Chapel Lane, Congerstone
	Area	1.26 hectares
	Current land use	Greenfield
	Proposed land use	Residential
NPPF and planning implications	Exception Test requirements	<p>The Sequential Test will need to be passed before the Exception Test is applied. The Exception Test will need to be applied if:</p> <ul style="list-style-type: none"> • More Vulnerable and Essential Infrastructure development is located in FZ3a and for Highly Vulnerable development located in FZ2. • Highly Vulnerable infrastructure should not be permitted within FZ3a and FZ3b. • More Vulnerable and Less Vulnerable Infrastructure should not be permitted within FZ3b. • Essential Infrastructure in Flood Zone 3b will require the Exception Test. <p>Residential development is classified as 'More Vulnerable'.</p>

	<p>Requirements and guidance for site-specific Flood Risk Assessment</p>	<ul style="list-style-type: none"> • Consultation with the Local Authority, Local Lead Flood Authority and the Environment Agency should be undertaken at an early stage. • At the planning application stage, a site-specific Flood Risk Assessment will be required if any development is located within Flood Zones 2 or 3 or is greater than one hectare. A Flood Risk Assessment must consider the entire lifetime of the development and consider all sources of flooding. • The site area includes the Flood Zone 2 extents. Most development types are appropriate for this flood risk zone but must take into account the flood risk (1% to 0.1% annual exceedance probability). • The site area includes the Flood Zone 3a extents. Future development must take into account the flood risk in this area (5% to 1% annual exceedance probability). More vulnerable and critical infrastructure development is possible within Flood Zone 3a but is required to pass the Exception Test. Highly vulnerable development is not permitted within Flood Zone 3a. • The site area includes the extents of Flood Zone 3b, also known as the functional floodplain. Only essential infrastructure passing the Exception Test is permitted within Flood Zone 3b. Should there be any development within Flood Zone 3b flood storage lost by the development must be offset. • An ordinary watercourse is within or immediately adjacent to the site area and therefore consultation with Lead Local Flood Authority should be completed. If alterations or discharges are proposed to the watercourse a land drainage consent will be required. • More detailed hydraulic modelling using channel survey may be required as part of a site-specific Flood Risk Assessment, to confirm flood risk shown in the 2D generalised modelling. • Resilience measures will be required if buildings are situated in the flood risk area through the centre of the site's boundary. Raising Finished Floor Levels above the design event may remove the need for resilience measures. • Onsite attenuation schemes would need to be tested against the drainage channel along the northern boundary of the site to ensure flows are not exacerbated downstream within the catchment. • New or re-development should adopt exemplar source control SuDS techniques to reduce the risk of frequent low impact flooding due to post-development runoff. • Water quality requirements for sustainable development should comply with current SuDS guidance. • Assessment for runoff should include allowance for climate change effects. • Safe access and egress will need to be demonstrated. • New development must seek opportunities to reduce overall level of flood risk at the site, for example by: <ul style="list-style-type: none"> ○ Reducing volume and rate of runoff ○ Relocating development to zones with lower flood risk ○ Creating space for flooding.
Mapping Information		
Flood Zones	The Flood Zones have been derived from 2D generalised modelling techniques.	
Climate change	The climate change allowances for the '2080s' epoch were modelled using 2D generalised modelling techniques.	
Surface Water	The Environment Agency's Risk of Flooding from Surface Water has been used to define areas at risk from surface water flooding.	
Fluvial depth, velocity and hazard mapping	Depth, velocity and hazard mapping for the 1 in 100-year event (Flood Zone 3a) have been taken from 2D generalised modelling techniques.	

**Hinckley and Bosworth Borough Level 2
Strategic Flood Risk Assessment:
Detailed Site Summary Tables**



Site details	Site Code	Site LPR79 – Land north and west of Chapel Lane, Congerstone
	Area	1.26 hectares
	Current land use	Greenfield
	Proposed land use	Residential
Surface water depth, velocity and hazard mapping		The surface water depth, velocity and hazard mapping for the 1 in 100-year event (considered to be medium risk) is taken Environment Agency's Risk of Flooding from Surface Water.